

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

## CLAIMS

1. A soft furnishing assembly comprising an intermediate portion having opposed ends, and at least one end portion connected to an end of the intermediate portion, the or each end portion being connected to the intermediate portion by a frangible portion, wherein the or each end portion is moveable between a first position in which the soft furnishing assembly is substantially flat and a second position in which the or each end portion angularly abuts an adjacent end of the intermediate portion and the frangible portion is broken.
2. A soft furnishing assembly in accordance with claim 1, wherein the intermediate portion and the or each end portion are provided with a channel, the channel being disposed linearly substantially along the length of a rear surface of the intermediate portion and of a rear surface of the or each end portion, the channel being arranged to receive a support member.
3. A soft furnishing assembly in accordance with claim 2, wherein a plurality of fastening members extend outwardly from the channel, the fastening members being arranged to engage with apertures provided on sides of the support member when received by the channel.
4. A soft furnishing assembly in accordance with claim 1, wherein the or each end portion has an inclined surface, proximal to a respective end surface of the intermediate portion, the inclined surface of each end portion being the same length as the adjacent end surface, the inclined surface and end surface defining a substantially V-shaped groove, whereby the frangible portion is disposed at a

trough of the V-shaped groove when the soft furnishing assembly is in the first position.

5. A soft furnishing assembly in accordance with claim 1, wherein the intermediate portion and the or each end portion is upholstered with a fabric.
6. A soft furnishing assembly in accordance with claim 5, wherein the soft furnishing assembly is provided with a fabric tensioning means in the form of a flexible cord arranged along the length of the groove at the rear of the soft furnishing assembly, the flexible cord being attached at a first end to a portion of fabric that protrudes from the groove when the soft furnishing assembly is placed in the second position and attached at an intermediate portion to an opposing portion of fabric protruding from the groove, whereby the flexible cord is tensioned before securing a second end of the flexible cord to the rear of the soft furnishing assembly, such that upon the or each end portion being moved into the second position, the fabric tensioning means prevents fabric from protruding from the groove when the soft furnishing assembly is in the second position.
7. A soft furnishing assembly in accordance with claim 6, wherein the flexible cord is attached at respective ends to a pair of opposing hook members, the hook members being arranged to project from opposing portions of fabric protruding from the groove.
8. A soft furnishing assembly in accordance with claim 2, wherein each end portion comprises a first portion and a second portion, the first and second portions being connected by a second frangible portion, wherein the first and the second portions are moveable between a first position in which the soft furnishing assembly is substantially flat and a second position in which the or each second frangible

portion is broken and the support member is received by the channel on each of the first and second portions.

9. A soft furnishing assembly in accordance with claim 8, wherein the support member comprises a first support member portion and a second support member portion, the first and second support member portions being releasably connected to one another.
10. A soft furnishing assembly in accordance with claim 9, wherein the second support member portion is arranged to be removed and the or each second portion is arranged to be disposed about the first support member portion such that the second portion is substantially parallel with the intermediate portion.
11. A soft furnishing assembly according to claim 1, wherein the assembly is a pelmet assembly
12. A method of construction of a soft furnishing assembly, comprising an intermediate portion having opposed ends, and at least one end portion connected to an end of the intermediate portion, the or each end portion being connected to the intermediate portion by a frangible portion, the method comprising the steps of:
  - engageably arranging a support member upon a rear surface of the intermediate portion;
  - moving the or each end portion about an end of the intermediate portion such that the or each end portion moves from a first position in which the soft furnishing assembly is substantially flat to a second position in which the or each end portion angularly abuts the adjacent end of the intermediate portion which causes the or each frangible portion to break; and

- fastening the or each end portion to a side of the support member.

13. A method according to claim 12, wherein the soft furnishing assembly is a pelmet assembly.